

# MIN 7000~10000 TL-X

- Maximum efficiency 98.1%
- 2/3 MPP trackers
- Type II SPD on DC side
- Supports export control
- Touch key and OLED display



**GROWATT**

P O W E R  
- I N G  
T O M O -  
R R O W

Datasheet	MIN 7000TL-X(E)	MIN 8000TL-X(E)	MIN 9000TL-X	MIN 10000TL-X
<b>Input data (DC)</b>				
Max. recommended PV power (for module STC)	12000W	12000W	13500W	15000W
Max. DC voltage				600V
Start voltage				100V
Nominal voltage				360V
MPP voltage range				60-550V
No. of MPP trackers	2		3	
No. of PV strings per MPP tracker	1/2		1/1/2	
Max. input current per MPP tracker	13.5A/27A		13.5A/13.5A/27A	
Max. short-circuit current per MPP tracker	16.9A/33.8A		16.9A/16.9A/33.8A	
<b>Output data (AC)</b>				
AC nominal power	7000W	8000W	9000W	10000W
Max. AC apparent power	7000VA	8000VA	9000VA	10000VA
Nominal AC voltage(range*)	Default:240V split-phase, optional:208V & 240V single phase , 183-228@208V 211-264V@240V			
AC grid frequency(range*)	50/60 Hz (45-55Hz/59.5-60.5Hz)			
Max. output current	33.5A	38.3A	43A	45.5A
Adjustable power factor	0.8leading...0.8lagging			
THDI	<3%			
AC grid connection type	Single phase			
<b>Efficiency</b>				
Max. efficiency			98.1%	
European efficiency	97.3%		97.6%	
MPPT efficiency			99.5%	
<b>Protection devices</b>				
DC reverse polarity protection			Yes	
DC switch			Yes	
DC/AC surge protection			Type II / Type III	
Insulation resistance monitoring			Yes	
AC short-circuit protection			Yes	
Ground fault monitoring			Yes	
Grid monitoring			Yes	
Anti-islanding protection			Yes	
Residual-current monitoring unit			Yes	
AFCI protection			Yes	
<b>General data</b>				
Dimensions (W / H / D)	425/387/180mm			
Weight	18.2kg			
Operating temperature range	- 25 °C ... +60 °C			
Nighttime power consumption	< 1W			
Topology	Transformerless			
Cooling	Natural convection			
Protection degree	IP66			
Relative humidity	0-100%			
Altitude	4000m			
DC connection	H4/MC4(Optional)			
AC connection	Cable gland +OT terminal			
Display	OLED+LED/WIFI+APP			
Interfaces: RS485 / USB/Wi-Fi/ GPRS/ RF/LAN	Yes/Yes/Optional/Optional/Optional /Optional			
Warranty: 5 years / 10 years	Yes/Optional			

CE, IEC 62116, IEC 61727, IEC62109, INMETRO, AS4777, UL1741, IEEI1547

\* The AC voltage and frequency range may vary depending on specific country grid standard. All specifications are subject to change without notice.